




---

**AEC PREMIER COCONUT™ FIBRENET™  
MATERIAL SPECIFICATIONS**

**Materials:**

Coconut  
Biodegradable Jute Netting

**Roll Sizes:**

Width:	8.0 ft (2.4 m)
Length:	112.5 ft (34.3 m)
Area:	100.0 yd <sup>2</sup> (83.6 m <sup>2</sup> )
Weight:	50.0 lb (22.7 kg)

**Description:**

AEC Premier Coconut FibreNet erosion control blanket (ECB) is a natural, stitched coconut blanket with 100% biodegradable Jute netting that provides a temporary organic cover to reduce erosion, protect seeds, enhance germination, and hasten re-vegetation. Product is 100% biodegradable. AEC Premier Coconut FibreNet rolls are stretch wrapped to protect against the elements prior to installation, and may be ordered in Master-Paks of fifteen rolls banded together to minimize handling requirements. ECB shall be Manufactured in the U.S.A.

AEC Premier Coconut FibreNet has a design soil loss ratio (event-based RUSLE C factor) of .10 and is typically suitable for slopes up to 1:1. AEC Premier Coconut FibreNet is rated for channel flows up to 9.0 ft/s (2.7 m/s) and 2.25 lb/ft<sup>2</sup> (108 Pa) shear stress.

**Physical Properties:**

Fiber: Coconut  
 Weight\*: 0.50 lb/yd<sup>2</sup> (0.27 kg/m<sup>2</sup>) ± 10%  
 Thread Pattern: No more than 2.0" (5.1 cm) transverse stitch spacing  
 Net Material: Biodegradable Jute  
 Net Openings: ≈ 0.50" wide x 0.50" long (12.7 mm x 12.7 mm)  
 Net Configuration: Top and bottom

\* Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of AEC Premier Coconut fibers is 20%.





---

**MANUFACTURER'S CERTIFICATION**

**AEC PREMIER COCONUT™ FIBRENET™ - Erosion Control Blanket**

**Manufacturer:**

American Excelsior Company  
831 Pioneer Avenue  
Rice Lake, WI 54868  
1-866-9FIBERS (1-866-934-2377)

**Project Information (if applicable):**

**Name:**

**Location:**

**Number:**

**Statement**

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Fiber:	Coconut
Blanket Length:	-0' (m), + 5% (upon application)
Blanket Width:	-0" (mm) + 1.0" (25.4 mm)
Weight*:	0.50 lb/yd <sup>2</sup> (0.27 kg/m <sup>2</sup> ) ± 10%
Thread Pattern:	No more than 2.0" (5.1 cm) transverse stitch spacing
Net Material:	Biodegradable Jute
Net Openings:	≈ 0.50" wide x 0.50" long (12.7 mm x 12.7 mm)
Net Configuration:	Top and bottom

\* Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of AEC Premier Coconut fibers is 20%.

  
Rocky Van Gilder - V.P. of Wood Operations

10/12/11  
Effective Date

**Note:** This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from [www.Curlex.com](http://www.Curlex.com) at all times.

